



## WFP Bitumen Primer

### Solvent – based Bitumen Primer

<b>Product description</b>	WFP Bitumen Primer is a solvent-based unfilled Bitumen Coating, which is used as primer e.g. on aged bitumen. This material has a high content of solid.	
<b>Area of application</b>	WFP Bitumen Primer is used as primer for nearly all subsequent bitumen-based coats. Only use in outside areas. The substrate must be solid, load bearing and free of releasing agents.	
<b>Properties</b>	<ul style="list-style-type: none"><li>- <b>One-component, easy to apply</b></li><li>- <b>Applicable with trowel or spraying device</b></li><li>- <b>Thin</b></li><li>- <b>Solvent-based</b></li><li>- <b>Good adhesive power</b></li><li>- <b>Fast setting</b></li><li>- <b>Powder binding</b></li><li>- <b>Resistant to water-based solutions, dilute acids, salts Lime, cement a.o.</b></li><li>- <b>„Made in Germany“</b></li></ul>	
<b>Specification</b>	Base:	Bituminous emulsion, solvent
	Colour:	black
	Processing temperature:	from + 5°C to + 30°C
	Density:	approx.0.87 g/cm <sup>3</sup>
	Consistency:	liquid
	Setting time:	approx.. 1 hour depending on humidity, temperature, layer thickness and surface
	Consumption:	approx. 0,2 -0,3 l/m <sup>2</sup> depending on required protection and surface
<b>Delivery form</b>	10 l –metal buckets 45 packages on each pallet	
<b>Storage</b>	12 months (cool and dry in the original package)	

## **Application**

### **Preparation of the surface**

The surface must be dry load bearing, stable, and clean. Loose components, soil, release agents, formwork oil, grease and other adhesive reducing layers should be removed before the application of WFP Bitumen Primer. Damaged concrete and plaster areas, cracks should be renovated with WFP Multi Mortar first. Burrs and sharp edges have to be removed first.

### **Material**

Homogenize the WFP Bitumen Primer completely by stirring before processing. Coating is applied in one step by painting or spraying in cloisters. Clean working tools whilst in fresh condition with dissolvers. In case of skin contact please use handwash paste.

### **Recommended tools**

Brush, wide brush, spraying device, gloves, safety glasses

### **Remark**

The information complies with the current state of development. There is no claim for completeness. A professional and therefore successful processing of the products is not within our responsibility. We accept a warranty only for the quality of the products, but not for processing. It is the responsibility of the user to evaluate the suitability of our products for its purpose. Preliminary tests are recommended.